

MARYN INTERNATIONAL LTD. MATERIAL SAFETY DATA SHEET Product: EngineMAXX LA PAGE 1 of 7

SECTION I: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Product use:	EngineMAXX LA Used as a 1%, 3%, or 5% additive to conventional lubricants.
Manufacturer:	WYS Manufacturing Ltd. Bay 7 & 8, 4216 – 54th Ave. SE Calgary, Alberta T2C 2E3 Phone 1-403-252-2239 Canada
Supplier:	Maryn International Ltd. Bay 5 & 6, 4216 – 54th Ave. SE Calgary, Alberta T2C 2E3 Phone 1-403-252-2239 Canada
Emergency Phone Number:	CANUTEC – 24 hr Emergency No. 1-613-996-6666 Business Hour Number 1-403-252-2239 (Monday through Friday 8:00am to 4:30pm MST)
MSDS Prepared By	Z. Ansarizadeh Phone 1-403-252-2239
Date Prepared	September 5, 2008

SECTION II: COMPOSITION/ INFORMATION ON INGREDIENTS

Hazardous Ingredients	Concentration %	C.A.S. #	LD50 (Species/Route)	LC50 (Species/Route)
Acrylic Copolymer	1-5%	Trade Secret	NA	NA
Dioctyl Phthalate	1-5%	117-81-7	>30000 mg/kg (Rat/Oral) >24500 mg/kg (Rabbit/Dermal)	NA
Isopropylated Triphenyl Phosphate	0.1-1%	68937-41-7	NA	NA
Polyolester	0.1-1%	68424-328	NA	NA

NA: Not Available



SECTION III: Hazards Identification

Emergency Overview	Causes eye irritation. May cause skin, respiratory tract, and mucous membrane irritation. May cause nervous system effects.	
Route of entry	Inhalation, ingestion, skin and eye contact are the primary routes of exposure to this product.	
Ingestion	May cause nervous system effects. Ingestion of large amounts may cause intestinal blockage. If drawn into lungs from swallowing or vomiting, may cause bronchopneumonia or pulmonary edema.	
Inhalation	May cause respiratory tract and mucous membrane irritation as well as nervous system effects. If product is misted at elevated temperature, high concentration of vapour and/or mist may cause irritation, experienced as nasal discomfort and discharge.	
Skin Contact and absorption	Frequent or prolonged contact may irritate the skin and cause a skin rash.	
Eye Contact	Irritating to the eyes, but will not cause injury to the eye tissue.	
Effects of Chronic Exposure	Repeated exposure over prolonged periods of time may cause irritation to the skin and respiratory system. It may also cause liver, adrenal, thymus, reproductive, developmental, and neurological effects. Follow good industrial hygiene practices to avoid exposure.	
Effects of Acute Exposure	Product is irritation to the eyes. Breathing mist caused by high temperature or swallowing large quantities may be irritating to skin, respiratory system, mucous membranes and eyes.	

SECTION IV: First Aid Measures

Ingestion	Do not induce vomiting. If victim is conscious and alert, give 2-4 cups of water. Never give anything by mouth to an unconscious person. Call physician immediately.
Skin Contact	Remove contaminated clothing. Wash well with soap and water for at least 15 minutes. Launder clothes prior to re-use.
Inhalation	If excessive fumes, remove victim to fresh air. If not breathing, qualified personnel may provide artificial respiration. If no relief is obtained, consult physician.
Eye Contact	Flush with clean tepid water for 15 minutes keeping eyelids open. If irritation persists, consult physician.
Notes to Physician	Treat symptomatically.

SECTION V: Fire-Fighting Measures

Flammability Non flammable at ambient temperature. Liquid may burn at temperatures above flash point if exposed to an open flame.



MARYN INTERNATIONAL LTD. MATERIAL SAFETY DATA SHEET Product: EngineMAXX LA PAGE 3 of 7

Means of Extinction	Carbon dioxide foam, dry chemicals. Keep containers cool with water spray. When fighting fire, treat as petroleum product, wear full protective clothing, including NIOSH approved self-contained breathing apparatus. Avoid spreading with water flooding.
Flash Point (ASTM D92)	170°C (338°F)
Upper Flammability Limits	Not Determined.
Lower Flammability Limits	Not Determined.
Auto Ignition Temperature	Not Determined.
Hazardous Combustion Products	Oxides of carbon, phosphorous and chlorine, hydrogen chloride, hydrogen sulphide and dense smoke.
Fire and Explosion Hazards	None
Sensitivity to impact Static Discharge	None at normal temperatures below flash point. Do not cut, weld, or pressurize empty container. Container may explode in heat of fire.

SECTION VI: Accidental Release Measures

Personal Protection	Wear suitable protective equipment. Eliminate sources and or potential sources of ignition.
Environmental Precautions	Product has very low solubility in water. Do not flush to sewers, streams or other bodies of water. For disposal, see Section XIII.
Methods for cleaning up	Absorb on inert material such as sand, earth, vermiculite. Sweep up and collect in a suitable container for disposal. Observe government regulations.
Large spills	Stop leak if without risk. Dike to contain spill. Pump excess material into suitable container (metal drums, metal tanks, or such).

SECTION VII: Handling and Storage

- Handling Avoid excess heat, formation of oil mist, breathing vapours and mist from hot oil, and prolonged or repeated contact with skin
- Storage Store in a cool well ventilated area. Keep away from heat spark and open flame.

SECTION VIII: Exposure Controls / Personal Protection

Exposure Limits

If used in a way that generates a mist, observe the limits for mineral oil mist



MARYN INTERNATIONAL LTD. MATERIAL SAFETY DATA SHEET Product: EngineMAXX LA PAGE 4 of 7

Component	Exposure Limit (ACGIH)	Exposure Limit (OSHA)	Immediately Dangerous to Life and Health (IDLH)
Mineral Oil Mist	5 mg/m ³ TWA-TLV 10 mg/m ³ STEL-TLV	5 mg/m ³ TWA-PEL Not Established STEL-PEL	2500 mg/m ³
Dioctyl Phthalate	5 mg/m ³ TWA-TLV Not Established STEL-TLV	5 mg/m ³ TWA-PEL Not Established STEL-PEL	5000 mg/m ³

Engineering Controls	For normal application, special ventilation is not necessary. If user's operation generates mist, use ventilation to keep exposure to airborne contaminants below exposure limits	
Respiratory Protection	Use approved respirator with dual organic vapour / mist and particulate cartridge if vapour concentratio exceeds permissible exposure limit	
Eye Protection	Use chemical splash goggles if risk of splashing present.	
Skin Protection	Use rubber or plastic apron.	
Hand Protection	Use oil resistant gloves.	

SECTION IX: Physical and Chemical Properties

Physical State:	Liquid
Odour:	Mild petroleum odour
Appearance:	Clear, light amber
Odour Threshold:	Not established
Specific Gravity:	0.965 at 20°C (68°F)
Vapour Pressure:	<1.00 mm Hg at 20°C, It may be as low as < 0.02 mm Hg at 20°C
Vapour Density:	Not available
Evaporation Rate:	Not available
Boiling Point:	>230°C (>446°F)
Pour Point:	-35°C (-31°F)
Solubility in Water:	Insoluble
pH:	Not available
Partitioning Coefficient:	Not available

SECTION X: Stability and Reactivity

Chemical Stability:	Stable	
Incompatibility:	Avoid contact with oxidizing agents, reducing agents, alkali metals, alkaline earth metals and ignition	
	source. Iron, zinc and aluminium avoided at high temperatures.	
Reactivity:	No reactivity	
Reactivity:	No reactivity	
Polymerization:	Will not occur	
Decomposition Products: Oxides of carbon, phosphorous and chlorine, hydrogen chloride, hydrogen sulphide and dense smoke.		



SECTION XI: Toxicological Information

Effects of Acute and Chronic Exposure:	
Skin Contact	Frequent or prolonged contact may irritate the skin and cause a skin rash.
Skin Absorption	No evidence of adverse effects from available information. Prolonged contact may cause mild irritation.
Eye Contact	Irritating to eyes, but will not injure eye tissue.
Inhalation	May cause respiratory tract and mucous membrane irritation as well as nervous system effects. If product is misted at elevated temperature, high concentration of vapour and/or mist may cause irritation, experienced as nasal discomfort and discharge.
Ingestion	May cause nervous system effects. Ingestion of large amounts may cause intestinal blockage. If drawn into lungs from swallowing or vomiting, may cause bronchopneumonia or pulmonary edema.
Irritancy:	Irritating to the eyes. Frequent or prolonged contact may irritate skin. If misted, inhalation of mist may cause irritation.
Sensitization:	Repeated or prolonged contact may cause sensitization in some individuals.
Carcinogenicity:	This product contains material that has been listed as a carcinogen or potential carcinogen by either the National Toxicology Program, International Agency for Research on Cancer, or the Occupational Safety and Health Administration. Dioctyl Phthalate (117-81-7): ACGIH A3 – Confirmed animal carcinogen with unknown relevance to humans.
Reproductive Toxicity:	This product contains materials that have shown adverse reproductive effects in experimental animals. Reproductive studies in rats and mice: after oral administration indications of a fetotoxic effect and disturbances of the reproduction ability occurred.
Teratogenicity:	Boys of moms highly exposed to phthalates show stunted genitals. The higher the level of phthalates in the mothers during the final months of pregnancy, the less masculine their boys were when examined by paediatricians. (Pittsburgh Post-Gazette 5/27/05).
Embryotoxicity:	No information is available and no adverse effects are anticipated.
Mutagenicity:	No information is available and no adverse effects are anticipated.
Toxicologically Synergistic Products:	Not available.

SECTION XII: Ecological information

Environmental Fate:

No specific environmental fate data is available. This product is not expected to be readily biodegradable. **Environmental Effects:**

This product contains materials that are considered to be marine pollutants. Avoid releasing into the environment.



SECTION XIII: Disposal Consideration

RCRA 40 CFR 261 Classification Not listed

US EPA Waste Number / Classification Not available

Waste Disposal

Dispose of waste material in compliance with all federal, state, provincial and local regulations. Incinerate in a furnace or bury in an approved landfill where permitted under appropriate federal, provincial and local regulations.

SECTION XIV: Transport Information

Department of Transport: TDG – Canada DOT/TDG Proper Shipping Name:

DOT/TDG Hazard Class: Product Identification Number: Packing Group: DOT/TDG Labels: DOT/TDG Placards: Regulated under DOT Regulated under TDG. Environmentally hazardous substance, liquid, n. o. s. (Contains triaryl phosphates, isopropylated and tripehnyl phosphate.) 9 UN3082 III **Primary:** Miscellaneous **Subsidiary:** Marine Pollutant None required

SECTION XV: Regulatory Information

CPR Compliance:

This product has been classified in accordance with the hazard criteria of *the Controlled Products Regulations* and the MSDS contains all of the information required by those regulations.

OSHA Hazard Communication Standards 29CFR 1910.1200:

This product is not known to contain any of the carcinogens required to be listed under OSHA Hazards Communication Standards 29 CFR 1910.1200.

WHMIS Classification:

This is a controlled product under WHMIS.

D2A: Materials Causing Other Toxic Effects: Very Toxic D2B: Materials Causing Other Toxic Effects: Toxic

CERCLA:

Contains chemicals listed on CERCLA (40CFR 302.4). If this product is accidentally spilled, it is subject to special reporting under requirements of the Comprehensive Environmental Response and Liability Act. We recommend you also contact local authorities to determine if there may be other local reporting requirements. CAS 117-81-7: 100lb final RQ; 45.4kg final RQ

SARA Title III Section 311/312:

Under the provisions of Title III, Section 311/312 of the Superfund Amendments and Reauthorization Act, this product is classified into the following hazard category: **ACUTE**, **CHRONIC**, **IMMEDIATE**, **DELAYED**.

SARA Title III Section 313:

This product does contain more than 1 % of any of the chemical substances listed under SARA Section 313. CAS 117-81-7



RCRA:

Contains chemicals listed on the **RCRA** (40 CFR 261.33) for hazardous waste. CAS 117-81-7: waste number U028

NPRI:

Contains chemicals listed in the **NPRI** under Canadian EPA. CAS 117-81-7: Part 1A Substances

Chemical Inventory

Canada: The ingredients of this product are on the DSL. United States: The ingredients of this product are on the TSCA

SECTION XVI Other Information

HMIS Information			
Degree of Hazard	HMIS Rating		
4= Severe	Health 1*		
3= Serious	Flammability 1		
2= Moderate	Reactivity 0		
1= Slight			
0= Minimal			
*=Chronic			

Revision Information Prepared by: Maryn Research Phone: 1-403-252-2239 Effective Date: July 21, 2010 Supersedes: September 5, 2008 Revision: 6.0

Maryn International Ltd. (the "Company"), shall not be liable for any damages arising from the information contained on this data sheet howsoever caused, if the product in question is not employed in a normal or foreseeable use or circumstances. The Company shall not be liable for any indirect or consequential damages arising out of the use of the information contained on this data sheet howsoever caused.